

Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide

MP-7102(S)

Two-Line
IP Coded
Telephone



Features

Key:

- Dial keys - (0-9,*,#)
- Function Keys
M1, M2 service dial keys

Phone:

- Two levels receiver volume (NORMAL/HIGH)
- Two pre-set service dials

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



PRODUCT OPTIONS



MP-7102(S)

Two-Line IP Corded Telephone.
2 Guest Service Keys.

SPECIFICATIONS

Software

Easy Administration

- Web GUI
- Firmware upgrade via web

Codec

- Auto provisioning

Network Protocol

- G.711 (a-law; -law)
- PPPoE/ Static IP/ DHCP client
- ToS / VLAN IEEE 802.1 p/q
- HTTP server
- STUN (RFC 3489)

SIP

- SIP V2 (RFC3261)

Security

- Md5 for SIP authentication (RFC 2069 / RDC2617)

DTMF

- In-Band / Out-of-Band DTMF (RFC2833) / SIP info (RFC2976)

Voice Quality

- Jitter buffer

Tone

- Ring back tone (local), Busy tone, Dial tone

Hardware

Power

- PoE: IEEE 802.3af, non-isolation

Jacks

- 10/100 Rj45 LAN port x 1, Rj9 Handset jack x 1

Ethernet cable

- 9 feet x 1

Size and Weight

- Dimensions: 220mm(L)x150mm(W)x120mm(H) (8.6 7"x5.91"x4. 72")
- Weight: 1120g

REGULATORY

EMI

- USA: FCC Part 15B EU: EN55032

Safety

- EU: EN60950-1

EMC

- EU: En55024 IEC61000-4-4
- EN61000-3-2 IEC61000-4-5
- EN61000-3-3 IEC61000-4-6
- EN61000-4-2 IEC61000-4-8
- EN61000-4-3 IEC61000-4-11

RoHS

- Comply with Directive 2002/95/EC RoHS

Temperature

- (as amended by Commission Decision 2005/613/EC)

- **Storage:** Low Temperature at -10°C
High Temperature at +60°C
- **Operating:** Low Temperature at 0°C
High Temperature at +40°C