

Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide

VM-9X00-SMLT(S)

1 or 2 Line
Corded SIP
Speakerphone
4.3 inch Color
TouchScreen
DECT Technology



Features

- 1 or 2 Line Corded
- DECT Technology
- 4.3" Color TouchScreen
- Hearing Aid Compatible
- 8 Guest Service Softkeys
- Full Duplex Speakerphone
- Controls one remote extension
- Speaker and Ringer Volume Control
- Message Waiting Key with LED indicator
- Customizable Hotel Logo and Menu on Display
- Multiple Language Support (English, French, Spanish Italian, Chinese, Japanese.)
- Function Keys: Home, Emergency, Language, Speaker, Message, Redial, Volume Control
- Screen Display: Service Menu, Language Menu, Time and Date, Text or Multi media Message, Guest Service Menu, Room Service, Talk Time, Room Number, Restaurant.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



MODEL P/N

SVM-9100-SMLT One Line
SVM-9200-SMLT Two Line

SPECIFICATIONS

Power Adapter	<ul style="list-style-type: none"> • PoE module: IEEE 802.3af on Station 										
Jacks	<ul style="list-style-type: none"> • Input: 100-240 VAC Output 5V/3A (Optional) • RJ45 10/100 Mbs LAN • DC Jack • RJ45 10/100 Ethernet Port • RJ9 Handset • USB Type A (Optional) 										
Screen Base	<ul style="list-style-type: none"> • 4.3" Capacitive Touch Screen WSVGA Color TFT, Backlit 										
Dimensions	<ul style="list-style-type: none"> • 201mm(L) x 132mm(W) x 121mm(H) 										
Weight	<ul style="list-style-type: none"> • 425g 										
DECT Master	<ul style="list-style-type: none"> • DECT / GAP Compatible 										
RF Band	<ul style="list-style-type: none"> • EU Band 1881.792 (ch0) - 1897.344 (ch9) (10 Channels) • US Band 1921.536 (ch0) - 1928.448 (ch4) (5 Channels) 										
Channel Space	<ul style="list-style-type: none"> • 1728 Khz • Bit Rate 1150 Kbit/s 										
Tx Power	<ul style="list-style-type: none"> • 100mW • GFSK 										
Administration	<ul style="list-style-type: none"> • Web GUI • Auto Provisioning via TFTP • Firmware Upgrade via TFTP 										
Codec	<ul style="list-style-type: none"> • G.711 										
Network Protocol	<ul style="list-style-type: none"> • HTTP/DHCP Server • ToS VLAN IEEE 802.1 p/q • Static IP / DHCP Client IP assignment. 										
Security	<ul style="list-style-type: none"> • Web Login for web setup • MD5 for SIP 										
SIP	<ul style="list-style-type: none"> • SIP V2 (RFC3261) 										
Voice Quality	<ul style="list-style-type: none"> • CNG / Jitter Buffer PLC / Echo Canceller LEC/AEC 										
Regulatory	<table border="0"> <tr> <td>USA</td> <td>EUROPE</td> </tr> <tr> <td>FCC Part 15D</td> <td>EN 301406</td> </tr> <tr> <td>Part 15B</td> <td>EN 300386</td> </tr> <tr> <td></td> <td>EN 60950-1, 301406</td> </tr> <tr> <td></td> <td>EN 301489-1-6</td> </tr> </table>	USA	EUROPE	FCC Part 15D	EN 301406	Part 15B	EN 300386		EN 60950-1, 301406		EN 301489-1-6
USA	EUROPE										
FCC Part 15D	EN 301406										
Part 15B	EN 300386										
	EN 60950-1, 301406										
	EN 301489-1-6										
RF											
EMI											
SAR											
EMC											
PTSN	FCC TIA-968B & Part 68 TBR 21										
RoHS	<ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (2005/613/EC) 										
Temperature	<ul style="list-style-type: none"> • Storage • Operating <table border="0"> <tr> <td>Cold point at -10 C</td> <td>Cold point at 0 C</td> </tr> <tr> <td>Hot point at +60 C</td> <td>Hot point at +40</td> </tr> </table>	Cold point at -10 C	Cold point at 0 C	Hot point at +60 C	Hot point at +40						
Cold point at -10 C	Cold point at 0 C										
Hot point at +60 C	Hot point at +40										