

# hoteltelephones.com

Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide

AAX-4100

Single Line Analog Wall mount Emergency Phone



Single line analog wall mount phone.

Magnetic hook switch.

Faceplate with customizable hotel logo.

Coiled cord with bungee cord (anti-drop string).

Phone: +44(0) 1908 682180 Email: info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





## **AEi-Corporate Office**

Carrollton, Texas , U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

#### AEi-EMEA Office

London, United Kindom Sales: +44 (0)1753.643736 emea@aeicommunications.com

### **AEi-Asia Pacific Office**

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

#### AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern. europe @aei communications. com

## **AEi-Corporate Office**

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

## 1. Features

Phone Features

Ring indicator

## 2. Hardware Specifications

LED Indications

Red color ring indicator

Power

Telephone line powered

Ring Voltage

40V RMS minimum

Jacks

RJ11 PSTN jack x 1

Line cord

0.7 feet x 1

Size and Weight

RoHS

Dimensions:200mm(L) x82mm(W) x 46mm(H), Weight: 450g

3. Regulatory ΕU USA

> **PSTN** Part 68 **TBR 21**

FCC Part 15B EN55032 & EN55024 **EMI** 

Telecom TIA/EIA 968 compliant

Temperature Storage: Low temperature at -10°C

High temperature at +60°C

Operating Low temperature at +5°C High temperature at +35°C

Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website.

Phone: +44(0) 1908 682180 Email: info@hoteltelephones.com

Model:

**AAX-4100** 

**AAX-4100-BC** 





