

## AFT-4100

Single Line Analog  
Wall mount Phone



- Single line analog wall mount phone.
- Magnetic hook switch.
- Faceplate with customizable hotel logo.
- Coiled cord.

Phone: +44(0) 1908 682180  
Email: [info@hoteltelephones.com](mailto:info@hoteltelephones.com)

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

- Phone Features
- Single Line
  - Ring indicator

## 2. Hardware Specifications

- LED Indications
- Red color ring indicator
- Power
- Telephone line powered
- Ring Voltage
- 40V RMS minimum
- Jacks
- RJ11 PSTN jack x 1, RJ9 Handset jack x 1
- Line cord
- 0.7 feet x 1
- Size and Weight
- Dimensions:200mm(L) x82mm(W) x 52mm(H), Weight: 450g

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968 compliant	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

[hoteltelephones.com](http://hoteltelephones.com)

Phone: +44(0) 1908 682180

For more information and to view our extensive range of hotel telephones please visit our website.

Email: [info@hoteltelephones.com](mailto:info@hoteltelephones.com)

Model:

AFT-4100

AFT-4100-BC



SFT-1100

Single Line  
SIP Phone



- Single line SIP wall mount phone.
- Magnetic hook switch.
- Faceplate with customizable hotel logo.
- Coiled cord with bungee cord (anti-drop string).

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

Phone Features	<ul style="list-style-type: none"> <li>Red color ring indicator</li> </ul>	
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI</li> <li>Auto provisioning via TFTP</li> <li>Phone remote resetting</li> </ul>	<ul style="list-style-type: none"> <li>Firmware upgrade via TFTP</li> <li>Phone status monitoring system</li> </ul>
Codec	<ul style="list-style-type: none"> <li>G.711 (a-law, <math>\mu</math>-law)</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>HTTP server</li> <li>ToS / VLAN IEEE 802.1 p/q</li> </ul>	<ul style="list-style-type: none"> <li>Static IP, DHCP Client</li> </ul>
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>	
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	

## 2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> <li>Ring indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE : IEEE 802.3af compliant</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>0.5 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:200mm(L) x82mm(W) x 52mm(H), Weight: 455g</li> </ul>

## 3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN 60950-1	
EMC		EN55024	EC61000-4-4
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	<ul style="list-style-type: none"> <li>Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>		
Temperature	<ul style="list-style-type: none"> <li>Storage: Low temperature at -10°C</li> <li>Operating Low temperature at +5°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +35°C</li> </ul>	

**Model:**

**SFT-1100**

**SFT-1100-BC**

