

Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide

ALN-5100

Single Line Analog
Emergency Phone



- Single line analog emergency phone.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

Phone: +44(0) 1908 682180
Email: info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.





AEi-Corporate Office
 Carrollton, Texas, U.S.A
 Sales: +1.254.335.0555
 sales@aeicomcommunications.com

AEi-EMEA Office
 London, United Kingdom
 Sales: +44 (0)1753.643736
 emea@aeicomcommunications.com

AEi-Asia Pacific Office
 New Taipei City, Taiwan
 Sales: +886.2.2696.8809
 asiapac@aeicomcommunications.com

AEi-CEE&CIS Office
 Budva, Montenegro
 Sales: +382 69 891 251
 eastern.europe@aeicomcommunications.com

AEi-Corporate Office
 Penang, Malaysia
 Sales: +604.3994341
 so.asia@aeicomcommunications.com

1. Features

- | | | |
|----------------|---|--|
| Keys | • Function keys | Volume up/down |
| Phone Features | <ul style="list-style-type: none"> • Red color message waiting indicator for ringing and message waiting • Handset volume control | <ul style="list-style-type: none"> • Ringer volume switch • Selectable flash timing 100ms, 300ms and 600 ms (by hardware setting, default is 600 ms) |

2. Hardware Specifications

- | | |
|-----------------|--|
| LED Indications | • Message waiting indicator |
| Power | • Telephone line powered |
| Ring Voltage | • 40V RMS minimum |
| Jacks | • RJ14 PSTN jack x 1 ,RJ9 Handset jack x1 |
| Line cord | • 10 feet x 1 |
| Size and Weight | • Dimensions:224mm(L) x108mm(W) x 128mm(H), Weight: 745g |

3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024 EN60950-1
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Telecom	• TIA/EIA 968-B compliant	
Temperature	<ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating Low temperature at +5°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +35°C

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website.

Phone: +44(0) 1908 682180

Email: info@hoteltelephones.com

Model:

ALN-5100



SLN-1100

Single Line SIP
Emergency Phone



- Single line SIP emergency phone.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

Phone: +44(0) 1908 682180
Email: info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	● Function keys	Volume up/down,
Phone Features	● Red color message waiting indicator for ringing and message waiting	● Handset and ringer volume control
Easy Administration	● Web GUI.	● Firmware upgrade via web.
	● Auto provisioning	
Codec	● G.711 (a-law, μ -law)	
Network Protocol	● HTTP server	● Static IP, DHCP Client
	● ToS / VLAN IEEE 802.1 p/q	
SIP	● SIP V2 (RFC3261)	
Security	● Web login authentication for web setup	● MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF	● In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Voice Quality	● CNG: Comfortable noise generator	
	● Echo canceller: LEC / AEC	
	● Jitter buffer/PLC	
Tones	● Ring back tone (local), Busy tone, Dial tone	

2. Hardware Specifications

LED Indications	● Message waiting indicator
Power	● PoE : IEEE 802.3af compliant ● AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	● RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1
Size and Weight	● Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g

3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN60950-1	
EMC		EN55024	
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	● Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)		
Temperature	● Storage: Low temperature at -10°C	High temperature at +60°C	
	● Operating Low temperature at +5°C	High temperature at +35°C	

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website.

Model:

SLN-1100



Phone: +44(0) 1908 682180

Email: info@hoteltelephones.com