



# CARRINGTON

[hoteltelephones.com](http://hoteltelephones.com)

The GPO Carrington is a suave but contemporary, classic design. This British telephone has just the right amount of 1920s decor, combined with modern technology. The design is based on the vintage Bakelite telephone and features push-button dialing, a pull-out pad tray (originally used for keeping note of exchange numbers) and authentic bell ring.

#### FEATURES:

- ▶ Authentic bell ring
- ▶ Classic early 20th century design
- ▶ Push-button dialing
- ▶ Pull-out note-pad tray
- ▶ Ringer on / off switch
- ▶ Compatible with modern telephone banking
- ▶ Available in Black, Chrome, Ivory and Red.

For more information and to view our extensive range of hotel telephones please visit our website.

Phone: +44(0) 1908 682180

Email: [info@hoteltelephones.com](mailto:info@hoteltelephones.com)







# CARRINGTON SIP



The GPO Carrington is a suave but contemporary, classic design. This British telephone has just the right amount of 1920s decor, combined with modern technology. The design is based on the vintage Bakelite telephone and features push-button dialing and a pull-out pad tray (originally used for keeping note of exchange numbers).

## FEATURES:

- ▶ Jacks: 10/100 RJ45 WAN, RJ9 Handset
- ▶ Dimensions: Width 16.0cm Depth 16.5cm Height 22.5cm
- ▶ Weight: 850grams
- ▶ Easy: GUI
- ▶ Administration: Web Based speed-dial key setting for m1-m6
- ▶ Firmware Upgrade via Web
- ▶ Auto Provisioning
- ▶ IP Address auto announcement from Handset
- ▶ Codec: G.711a/u-low/G.723/G.729
- ▶ Network Protocol: Telnet / http Server / DNS Client
- ▶ PPPoE / Static / DHCP Client IP assignment.
- ▶ ToS field / VLAN IEEE 802.1 p/q
- ▶ SIP: SIP V1 (RFC2543) SIP V2 (RFC3261)
- ▶ Security: Web Login authentication for web setup
- ▶ MD5 for SIP authentication (RFC2069/ RFC2617)
- ▶ Voice Quality: CNG Comfortable Noise Generator
- ▶ LEC Line Echo Canceller: Jitter Buffer
- ▶ VAD Voice Activity Detection: Packet Loss Compression
- ▶ EMI USA: FCC Part 15B,D ICES-003 EU: EN 55022
- ▶ EMC EU: EN 55024, EN 61000-4-4, EN 61000-3-2, IEC 61000-4-5
- ▶ EN 61000-3-3, IEC 61000-4-6, EN 61000-4-2, IEC 61000-4-11
- ▶ RoHS: Comply with directive 2002/95/ EC RoHS (2005/613/EC)
- ▶ Temperature Storage Operating: -10C to +60C 0C to +40C.

For more information and to view our extensive range of hotel telephones please visit our website.