

hoteltelephones.com

Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide

MIP-300

Wi-Fi Phone for FOH/BOH





- Push to talk.
- Phone book.
- Headset Jack
- Vibrate in silent mode
- Portable compact design.
- Wi-Fi 2.4Ghz, IEEE 802.11 b/g/n
- WEP/WPA/WPA2 Wi-Fi encryption

Phone: +44(0) 1908 682180 Email: info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas, U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

AEi-EMEA Office

London, United Kindom Sales: +44 (0)1753.643736 emea@aeicommunications.com

AEi-Asia Pacific Office

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

AEi-Corporate Office

Redial last call

SSID scan Blind transfer

Talking Time Caller ID

Wireless Signal Strength

Ringing indicator

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

1. Features

Easy Administration

Keys Dial keys (0~9, *, #)

> Function keys Call, End/Power On/Off, 4 ways navigation key, Volume control keys

Soft keys Right/Left soft key

Phone Features Phonebook

Handset and ringer volume control

Voice message with red indicator I

Call history (incoming / outgoing / Missed calls)

Push to talk(Group talk)

Display Contents White backlight graphic monochrome LCD (112

Battery Level, Charge Indication

Auto provisioning via TFTP

2.4GHz, IEEE 802.11 b/g/n Wi-Fi client

Wi-Fi Standard

Wi-Fi Encryption WEP, WPA_PSK, WPA2_PSK, WPA_WPA2_PSK, WPA2_ENTERPRISE

> Codec G.711u/a, G.729

Network Protocol Static IP, DHCP Client

IPv4.

SIP SIP V2 (RFC3261)

Security MD5 for SIP authentication (RFC2069/ RFC2617)

DTMF In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)

Voice Quality CNG: Comfortable noise generator

Echo canceller: LEC / AEC

Jitter buffer/PLC

Tones Ring back tone (local), Busy tone

2. Hardware Specifications

Display Graphic 112 x 64 monochrome LCD with white backlight

LED Indications Message indicator(red)

> Power 3.7v / 900 mAh Li-ion battery

Standby Time: 40 hrs

Continuous talking Time: 200 mins

AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 500mA (Micro USB)

Jacks

Micro USB x 1; Headset x 1

Accessories

Belt clip, Charging cradle, Headset, Leather case

Dimensions: 128mm(L) x 47mm(W) x 27mm(H); Weight: 120g Size and Weight

Regulatory USA

> FCC Part 15B **EMI** EN300328 FCC Part 15C Safety EN60950-1

EN301489-1 **EMC** EN301489-17

RoHS Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)

Temperature Storage: Low temperature at -10°C High temperature at +60°C Operating Low temperature at +5°C High temperature at +35°C

hoteltelephones.com

Model: **MIP-300**

Phone: +44(0) 1908 682180

For more information and to view our extensive range of hotel telephones please visit our website





Email: info@hoteltelephones.com