

hoteltelephones.com

Single Line Analog phone

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

RW-5102(A)

Basic single-line corded analog phone

- Faceplate with customizable hotel logo
- 2 non volatile one-touch programmable speed dial buttons

Phone: +44(0) 1908 682180 Email: info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

mmmmmm

At AEi your satisfaction is our priority.





AEi-Corporate Office

Carrollton, Texas , U.S.A Sales: +1.254.335.0555 sales@aeicommunications.com

AEi-EMEA Office London, United Kindom Sales: +44 (0)1753.643736 emea@aeicommunications.com **AEi-Asia Pacific Office**

New Taipei City, Taiwan Sales: +886.2.2696.8809 asiapac@aeicommunications.com

AEi-CEE&CIS Office

AEi-Corporate Office Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

Budva, Montenegro Sales: +382 69 891 251 eastern.europe@aeicommunications.com

Keys	 Dial keys 	(0~9, *, #)			
	 Function keys 	2 speed dial keys			
Phone Features	Basic single line telephone system				
	Two levels receiver volume(NORMAL/HIGH)				
	Two levels ringer switch				
	2 non volatile one-touch programmable speed dial buttons				
	Tone dialing only				
	Hearing aid receive	er compliant PBX/ Stand	dard line compatible		
. Hardware Spec	ifications				
Power		vered (without AC adap	tor or battery)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Ring Voltage • 40V RMS minimum					
Jacks RJ11 PSTN jack x 1, RJ9 Handset jack			1		
Line cord • 0.7 feet x 1					
Size and Weight		n(L) x150mm(W) x 120	mm(H) Weight: 1160g		
	Dimonologici		(i), troigin: 1100g		
. Regulatory	US	A		EU	
PSTN	Part 68		TBR 21		
EMI	FCC Part 15B		EN55032 & EN55024 EN62368-1		
RoHS •	Comply with directive 2	2002/95/EC RoHS (as a	amended by commissio	on decision 2005/613/EC	
Telecom •	TIA/EIA 968-B complia	Int			
Temperature •	Storage: Low temperature at -10°C		High temperatu	High temperature at +60°C	
	Operating Low tempe	rature at +5°C	High temperatu	re at +35°C	

hoteltelephones.com

Phone: +44(0) 1908 682180

For more information and to view our extensive range of hotel telephones please visit our website.

T

Email: info@hoteltelephones.com



οHS

Specifications are subject to change without notice. Design Patent Pending©2018 AEI Communications. All rights reserved.