

Serving the Hospitality Industry with Advanced  
**IP and Analog** Telephony Solutions  
**Worldwide**

SLN-1100

SLN-1200

1 or 2 Lines  
SIP Phone



- 1 or 2 lines SIP phone.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

Phone: +44(0) 1908 682180  
Email: [info@hoteltelephones.com](mailto:info@hoteltelephones.com)

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

	Keys	1200	1100
		● Dial keys (0~9, *, #)	(0~9, *, #)
		● Line keys Line1, Line2 with LED, End	N/A
		● Function keys Hold, Redial, Volume up/down	Volume up/down,
Phone Features		● One or Two Lines	● Handset and ringer volume control
		● Red color message waiting indicator for ringing and message waiting	● Redial last call(1200)
			● Call Hold and resume(1200)
Easy Administration		● Web GUI.	● Firmware upgrade via web.
		● Auto provisioning	
Codec		● G.711 (a-law, μ-law)	
Network Protocol		● HTTP server	● Static IP, DHCP Client
		● ToS / VLAN IEEE 802.1 p/q	
SIP		● SIP V2 (RFC3261)	
Security		● Web login authentication for web setup	● MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF		● In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Voice Quality		● CNG: Comfortable noise generator	
		● Echo canceller: LEC / AEC	
		● Jitter buffer/PLC	
Tones		● Ring back tone (local), Busy tone, Dial tone	

## 2. Hardware Specifications

LED Indications	● Line keys and Message waiting indicator
Power	● PoE : IEEE 802.3af compliant ● AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	● RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1
Size and Weight	● Dimensions: 224 (L) x 108mm(W) x 124mm(H), Weight: 770g

## 3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN60950-1	
EMC		EN55024	EC61000-4-4
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	● Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)		
Temperature	● Storage: Low temperature at -10°C	High temperature at +60°C	
	● Operating Low temperature at +5°C	High temperature at +35°C	

[hoteltelephones.com](http://hoteltelephones.com)

For more information and to view our extensive range of hotel telephones please visit our website.

**Model:**

**SLN-1100**

**SLN-1200**

Phone: +44(0) 1908 682180

Email: [info@hoteltelephones.com](mailto:info@hoteltelephones.com)

