

Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide


VM-8100-SMKLT(S)

1 or 2 Lines

Cordless Touch

VM-8200-SMKLT(S)

Screen SIP Phone



- 1 or 2 lines cordless phone.
- Magnetic hook switch.
- 4.3 inch touch screen.
- Multi language support
- Full duplex speakerphone.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.

Phone: +44(0) 1908 682180 | Email:
 info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi-Corporate Office
 Carrollton, Texas, U.S.A
 Sales: +1.254.335.0555
 sales@aeicomcommunications.com

AEi-EMEA Office
 London, United Kindom
 Sales: +44 (0)1753.643736
 emea@aeicomcommunications.com

AEi-Asia Pacific Office
 New Taipei City, Taiwan
 Sales: +886.2.2696.8809
 asiapac@aeicomcommunications.com

AEi-CEE&CIS Office
 Budva, Montenegro
 Sales: +382 69 891 251
 eastern.europe@aeicomcommunications.com

AEi-Corporate Office
 Penang, Malaysia
 Sales: +604.3994341
 so.asia@aeicomcommunications.com

1. Features

Handset

	8200	8100
Keys	<ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys Line1, Line2, END • Function keys SPEAKER, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys 	<ul style="list-style-type: none"> • (0~9, *, #) • Line, END • SPEAKER, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys
Phone Features	<ul style="list-style-type: none"> • One or Two Lines • 3 hard key and 7 scrollable service dials • Call Hold and resume(8200 only) • Handset, Speaker, and Ringer volume control 	<ul style="list-style-type: none"> • Full duplex speaker phone • Mute and unmute(8100 only) • Red color message waiting indicator for ringing and message waiting
Display Contents	<ul style="list-style-type: none"> • Main logo • Service dial list/icons • Battery status: power level, charging status 	<ul style="list-style-type: none"> • DECT signal status • Line status • Firmware Version
DECT Standard	<ul style="list-style-type: none"> • DECT / CAT iq2.0 compatible • Radio Frequency Range : 1880~1930 MHz • EU : 81.792(ch0)~1897.344(ch9) 10 Channels • US : 1921.536(ch0)~1928.448(ch4) 5 Channels • JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> • Channel Space : 1728 KHz • Bit rate : 1150 Kbit/s • Modulation : GFSK • Voice coding : 16 Kbit/s • RF power : 7 dBm

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

Phone: +44(0) 1908 682180
 Email: info@hoteltelephones.com



AEi-Corporate Office
 Carrollton, Texas, U.S.A
 Sales: +1.254.335.0555
 sales@aeicomcommunications.com

AEi-EMEA Office
 London, United Kingdom
 Sales: +44 (0)1753.643736
 emea@aeicomcommunications.com

AEi-Asia Pacific Office
 New Taipei City, Taiwan
 Sales: +886.2.2696.8809
 asiapac@aeicomcommunications.com

AEi-CEE&CIS Office
 Budva, Montenegro
 Sales: +382 69 891 251
 eastern.europe@aeicomcommunications.com

AEi-Corporate Office
 Penang, Malaysia
 Sales: +604.3994341
 so.asia@aeicomcommunications.com

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

Base		
	8200	8100
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE 	<ul style="list-style-type: none"> (0~9, *, #) N/A LANGUAGE, EMERGENCY, HOME, REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE
Phone Features	<ul style="list-style-type: none"> 4.3" TFT color touch screen Customizable service menu Call Hold and resume(8200 only) Red color message key with indicator Redial last call 	<ul style="list-style-type: none"> Speaker and ringer volume control Full duplex speaker phone Mute and unmute(8100 only) Multiple languages support Ringing indicator
Display Contents	<ul style="list-style-type: none"> Hotel logo Service menu Language menu Date and time Firmware version 	<ul style="list-style-type: none"> Talking time IP address MAC address SIP register status Failed network link warning Firmware upgrade via TFTP
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning via TFTP 	
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law) 	
Network Protocol	<ul style="list-style-type: none"> Static IP, DHCP Client HTTP server 	<ul style="list-style-type: none"> ToS / VLAN IEEE 802.1 p/q
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261) 	
Security	<ul style="list-style-type: none"> Web login authentication for web setup MD5 for SIP authentication (RFC 2069/ RFC2617) 	<ul style="list-style-type: none"> HTTPS TLS 1.2
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality	<ul style="list-style-type: none"> Echo canceller: LEC / AEC CNG: Comfortable noise generator 	<ul style="list-style-type: none"> Jitter buffer/PLC
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 881.792(ch0)~1897.344(ch9) 10 Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 17 dBm

Phone: +44(0) 1908 682180
 Email: info@hoteltelephones.com

2. Hardware Specifications

Handset

Display	• 2.0" TFT color display	
LED Indications	• Message waiting indicator and keypad backlight	
Power	• 3.7v / 900 mAh Li-ion battery	• Standby Time : 240 hrs
	• Charging Time : 5 hrs	• Talking Time: 9 hrs
Contact pins	• 3 contact pins for charging and hook detecting.	
Size and Weight	• Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)	

Base

Display	• Type	4.3" resistive touch WQVGA color TFT with backlight
	• Resolution	272 x 480 pixels
	• Display size W x H	55.5mm x 96.7mm
LED Indications	• Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys	
Power	• PoE : IEEE 802.3af compliant	
	• AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)	
Jacks	• RJ45 10/100 Mbs: LAN port x 1; DC jack x 1	
Contact pins	• 3 contact pins for charging and hook detecting.	
Ethernet cable	• 9 feet x 1	
Size and Weight	• Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 585g	

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60950-1
EMC		EN301489-1/6
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website.

Phone: +44(0) 1908 682180

Email: info@hoteltelephones.com

Model:

VM-8100-SMKLT-997901(S)

VM-8200-SMKLT-997901(S)

