


VM-8108-SMK(A)

VM-8208-SMK(A)

1 or 2 Lines
Cordless Analog
Phone



- 1 or 2 lines cordless phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.

Phone: +44(0) 1908 682180
Email: info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Handset

	Keys	8208	8108
	- Dial keys - Line keys - Function keys	(0~9, *, #) Line1, Line2, END SPEAKER, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys	(0~9, *, #) Line, END SPEAKER, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys
Phone Features	- One or Two Lines 3 hard key and 7 scrollable service dials - Call Hold and resume(8208 only) - Handset, Speaker, and Ringer volume control		- Full duplex speaker phone - Mute and unmute(8108 only) - Red color message waiting indicator for ringing and message waiting
Display Contents	- Main logo - Service dial list/icons - Battery status: power level, charging status		- DECT signal status - Line status - Firmware Version
DECT Standard	- DECT / CAT iq2.0 compatible - Radio frequency range : 1880~1930 MHz - EU:1881.792(ch0)~1897.344(ch9) 10 channels - US:1921.536(ch0)~1928.448(ch4) 5 channels - JP:1895.616(ch0)~1902.528(ch4) 5 Channels		- Channel space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 7 dBm

Base

	Keys	8208	8108
	- Dial keys - Line keys - Function keys	((0~9, *, #) Line1, Line2 with red color LED REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys	(0~9, *, #) N/A REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys
Phone Features	8 customizable service dials - Call Hold and resume(8208 only) - Handset, speaker and ringer volume control - Red color message key with indicator		- Mute and unmute(8108 only) - Redial last call - Ringing indicator - Full duplex speaker phone
DECT Standard	- DECT / CAT iq2.0 compatible - Radio frequency range : 1880~1930 MHz - EU:1881.792(ch0)~1897.344(ch9) 10 channels - US:1921.536(ch0)~1928.448(ch4) 5 channels - JP:1895.616(ch0)~1902.528(ch4) 5 Channels		- Channel space : 1728 KHz - Bit rate : 1150 Kbit/s - Modulation : GFSK - Voice coding : 16 Kbit/s - RF power : 17 dBm

2. Hardware Specifications

Handset

- | | | |
|-----------------|---|--------------------------|
| Display | • 2.0" TFT color display | |
| LED Indications | • Message waiting indicator and keypad backlight | |
| Power | • 3.7v / 900 mAh Li-ion battery | • Standby Time : 240 hrs |
| | • Charging Time : 5 hrs | • Talking Time: 9 hrs |
| Contact pins | • 3 contact pins for charging, hook detecting and auto-pairing | |
| Size and Weight | • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included) | |

Base

- | | |
|-----------------|--|
| LED Indications | • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys |
| Power | • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A |
| Jacks | • RJ14(RJ11) PSTN jack x 1, DC jack x 1 |
| Contact pins | • 3 contact pins for charging and hook detecting. |
| Line cord | • 10 feet x 1 |
| Size and Weight | • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 510g |

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60950-1
EMC		EN301489-1/6
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website.

Phone: +44(0) 1908 682180

Email: info@hoteltelephones.com

Model:

VM-8108-SMK(A)

VM-8208-SMK(A)

