

Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide

VM-9108-S(S)

VM-9208-S(S)

1 or 2 Lines
SIP Phone



- 1 or 2 lines SIP phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.

Phone: +44(0) 1908 682180
Email: info@hoteltelephones.com

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.





AEi-Corporate Office
 Carrollton, Texas, U.S.A
 Sales: +1.254.335.0555
 sales@aeicomcommunications.com

AEi-EMEA Office
 London, United Kingdom
 Sales: +44 (0)1753.643736
 emea@aeicomcommunications.com

AEi-Asia Pacific Office
 New Taipei City, Taiwan
 Sales: +886.2.2696.8809
 asiapac@aeicomcommunications.com

AEi-CEE&CIS Office
 Budva, Montenegro
 Sales: +382 69 891 251
 eastern.europe@aeicomcommunications.com

AEi-Corporate Office
 Penang, Malaysia
 Sales: +604.3994341
 so.asia@aeicomcommunications.com

1. Features

Keys	9208	9108
	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys 	<ul style="list-style-type: none"> (0~9, *, #) NA REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys
Phone Features	<ul style="list-style-type: none"> 8 customizable service dials Call Hold and resume(9208 only) Handset, speaker and ringer volume control Red color message key with indicator 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and unmute(9108 only) Redial last call Ringing indicator
Display Contents	<ul style="list-style-type: none"> Talking time IP Address MAC Address Date and time 	<ul style="list-style-type: none"> SIP Register Status Firmware Version Failed Network link Warning
Easy Administration	<ul style="list-style-type: none"> Web GUI Auto provisioning via TFTP 	<ul style="list-style-type: none"> Firmware upgrade via TFTP
Codec	<ul style="list-style-type: none"> G.711 (a-law, μ-law) 	
Network Protocol	<ul style="list-style-type: none"> HTTP server ToS / VLAN IEEE 802.1 p/q 	<ul style="list-style-type: none"> Static IP, DHCP Client
SIP	<ul style="list-style-type: none"> SIP V2 (RFC3261) 	
Security	<ul style="list-style-type: none"> Web login authentication for web setup MD5 for SIP authentication (RFC 2069/ RFC2617) 	<ul style="list-style-type: none"> HTTPS TLS 1.2
DTMF	<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality	<ul style="list-style-type: none"> CNG: Comfortable noise generator Echo canceller: LEC / AEC Jitter buffer/PLC 	
Tones	<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

Phone: +44(0) 1908 682180
 Email: info@hoteltelephones.com

2. Hardware Specifications

Display	• Dot matrix LCM 16 x 2 with backlight
LED Indications	• Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	• PoE : IEEE 802.3af compliant • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
Jacks	• RJ45 10/100 Mbs: LAN port x 1; DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	• 9 feet x 1
Size and Weight	• Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 630g

3. Regulatory

	USA	EU	
EMI	FCC Part 15B	EN55032	
Safety		EN60950-1	
EMC		EN55024	EC61000-4-4
		EN61000-3-2	EC61000-4-5
		EN61000-3-3	EC61000-4-6
		IEC61000-4-2	EC61000-4-8
		IEC61000-4-3	EC61000-4-11
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)		
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C	
	• Operating Low temperature at +5°C	High temperature at +35°C	

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website

Phone: +44(0) 1908 682180 | Email: info@hoteltelephones.com

Model:

VM-9108-S-9901(S)

VM-9208-S-9901(S)

