


Serving the Hospitality Industry with Advanced
IP and Analog Telephony Solutions
Worldwide

VX-8108-SMBU(A)

1 or 2 Lines
Cordless Analog
Phone

VX-8208-SMBU(A)



- 1 or 2 lines cordless phone.
- Full duplex speakerphone.
- Message waiting indicator.
- Pair up to 4 cordless remotes.
- Customizable hotel logo and service dials.
- 3 hard key and 7 scrollable service dials.
- Two USB charging ports.

Phone: +44(0) 1908 682180

Email: info@hoteltelephones.com

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.





AEI-Corporate Office
 Carrollton, Texas, U.S.A
 Sales: +1.254.335.0555
 sales@aeicomcommunications.com

AEI-EMEA Office
 London, United Kingdom
 Sales: +44 (0)1753.643736
 emea@aeicomcommunications.com

AEI-Asia Pacific Office
 New Taipei City, Taiwan
 Sales: +886.2.2696.8809
 asiapac@aeicomcommunications.com

AEI-CEE&CIS Office
 Budva, Montenegro
 Sales: +382 69 891 251
 eastern.europe@aeicomcommunications.com

AEI-Corporate Office
 Penang, Malaysia
 Sales: +604.3994341
 so.asia@aeicomcommunications.com

1. Features

Handset

	Keys	8208	8108
		<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2, END Function keys SPEAKER, VOLUME +/-, HOLD, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys 	<ul style="list-style-type: none"> (0~9, *, #) Line, END SPEAKER, VOLUME +/-, MUTE, MESSAGE, GUEST SERVICES, EMERGENCY, and 3 soft keys
	Phone Features	<ul style="list-style-type: none"> One or Two Lines 3 hard key and 7 scrollable service dials Call Hold and resume(8208 only) Handset, Speaker, and Ringer volume control 	<ul style="list-style-type: none"> Full duplex speaker phone Mute and unmute(8108 only) Red color message waiting indicator for ringing and message waiting
	Display Contents	<ul style="list-style-type: none"> Main logo Service dial list/icons Battery status: power level, charging status 	<ul style="list-style-type: none"> DECT signal status Line status Firmware Version
	DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 7 dBm

Base

DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq2.0 compatible Radio Frequency Range : 1880~1930 MHz EU : 1881.792(ch0)~1897.344(ch9) 10 Channels US : 1921.536(ch0)~1928.448(ch4) 5 Channels JP : 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 17 dBm
----------------------	--	--

	8208-SMBU-BB(A)	8108-SMBU-BB(A)	8208-SMBU(A)	8108-SMBU(A)
Battery Backup	Y	Y	N	N
USB Charger	Y*	Y*	Y	Y

*USB chargers will stop charging while power failure

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

Phone: +44(0) 1908 682180
 Email: info@hoteltelephones.com

2. Hardware Specifications

Handset

- Display • 2.0" TFT color display
- LED Indications • Message waiting indicator and keypad backlight
- Power • 3.7v / 900 mAh Li-ion battery • Standby Time : 240 hrs
- Charging Time : 5 hrs • Talking Time: 9 hrs
- Contact pins • 3 contact pins for charging and hook detecting
- Size and Weight • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included)

Base

- LED Indications • Handset charging indicators
- Power • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 3A (5V / 1A for USB charging)
- Optional battery backup while power failure
- Jacks • RJ14 PSTN jack x 1, DC jack x 1, USB type A x 2, Reset x 1
- Contact pins • 3 contact pins for charging and hook detecting
- Line cord • 10 feet x 1
- Battery backup • Power failure backup battery 3.7v / 900 mAh Li-ion (Optional)
- Charging time: 5hrs
- Supply standby time: 4hrs
- Supply talking time: 2hrs
- Power failure backup battery does not supply power to USB jacks
- Size and weight • Dimensions:115.7mm(L) x104.5mm(W) x 98.8mm(H), Weight: 340g(Base only)
- Dimensions:115.7mm(L) x104.5mm(W) x 190mm(H), Weight: 480g(Handset and base)

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN301406
EMI	FCC Part 15B	EN300386
SAR		EN62479
Safety		EN60368-1
EMC		EN301489-1/6
PSTN	Part 68	TBR21
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at +5°C	High temperature at +35°C

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website.

Phone: +44(0) 1908 682180

Email: info@hoteltelephones.com

Model:

VX-8108-SMBU(A)

VX-8208-SMBU(A)

VX-8108-SMBU-BB(A)

VX-8208-SMBU-BB(A)

