

SPACE-SAVING DESIGN. MONEY-SAVING VALUE.



NUGGET SERIES

Designed for tight spaces and tighter budgets.

Teledex Nugget 3

- Single Line Telephones
- ADA Handset Volume Boost – Compliant with HAC/VC and FCC requirements
- Data Port – Easy access for laptop modem or fax machine use
- Raised Red Message Waiting Lens – Easily seen from any area in the guestroom
- Paper Faceplate – Allows user-friendly customization
- MultiX™ Message Waiting Circuitry – Guarantees operation of up to 10 phones for suite applications, with an extra-bright message-waiting lamp
- Redial Key – Automatically redials the last number dialed
- Flash Function – Access to PBX functions
- Hidden Programming Key – Eliminates arbitrary reprogramming of autodial keys
- Textured Finish – Provides durable resistance against scratches and smudges
- Stylish Euro Handset – Complements room décor
- Desk or Wall Mountable – Provides placement flexibility



Teledex Nugget

- Single Line Telephones
- ADA Handset Volume Boost – Compliant with HAC/VC and FCC requirements
- Data Port – Easy access for laptop modem or fax machine use
- Raised Red Message Waiting Lens – Easily seen from any area in the guestroom
- Paper Faceplate – Allows user-friendly customization
- Flash Function – Access to PBX functions
- Textured Finish – Provides durable resistance against scratches and smudges
- Stylish Euro Handset – Complements room décor
- Desk or Wall Mountable – Provides placement flexibility with no additional parts



TELEDEX NUGGET SERIES

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Nugget 3) (Desk, Wall):	6.25" (15.88cm) (w) x 9.0" (22.86cm) (l) x 2" (5.08cm) (d) (without handset); 6.25" (15.88cm) (w) x 9.0" (22.86cm) (l) x 3.5" (8.89cm) (d) (with handset)
Footprint (Nugget) (Desk, Wall):	4.75" (12.07cm) (w) x 9.0" (22.86cm) (l) x 2" (5.08cm) (d) (without handset); 4.75" (12.07cm) (w) x 9.0" (22.86cm) (l) x 3.5" (8.89cm) (d) (with handset)
Weight:	1.4 lbs. (0.63kg)
Packaging:	10 per carton
Faceplate Size:	8.75" x 3.13"
FCC Specifications:	Meet or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard:	ETL and CE

Operating Voltage:	24 to 56 VDC
Signaling:	Non-Polarity Standard 12 tone
Flash Timing:	DTMF/pulse 600 ms
Ringer Equivalence:	Z
Cabling (Nugget 3):	1 pair minimum
(Nugget)	1 pair minimum
Registered Connector:	USOC RJ-11
Handset:	Hearing Aid compatible Standard or Euro type
Handset Cord:	10-foot coil cord
Line Cord:	12-foot, 1 pair

PART NUMBERS

NUGGET 3 SERIES

NUG31739..... Ash
NUG317391..... Black

NUGGET SERIES

NUG31039..... Ash
NUG310391..... Black

hoteltelephones.com

For more information and to view our extensive range of hotel telephones please visit our website.

Phone: +44(0) 1908 682180

| Email: info@hoteltelephones.com

U.S. Toll Free 1 800 794 8353
Telephone +1 719 638 8821
Fax +1 719 638 8815
info@teledex.com
teledex.com